

Plug & Receptacle Configuration Chart



NEMA

IEC

AMP	VOLT	STRAIGHT-BLADE PLUG	STRAIGHT-BLADE RECEPTACLE	AMP	VOLT	STRAIGHT-BLADE PLUG	STRAIGHT-BLADE RECEPTACLE
15	125			20	250		
20	125						
AMP	VOLT	TWIST-LOCK PLUG	TWIST-LOCK RECEPTACLE	AMP	VOLT	TWIST-LOCK PLUG	TWIST-LOCK RECEPTACLE
15	125			20	120/208 x 3-WYE		
20	125			20	230/400 x 3-WYE		
30	125			30	120/208 x 3-WYE		
20	250			30	230/400 x 3-WYE		
30	250			30	250 x 3-DELTA		
20	125 / 250			AMP	VOLT	CALIFORNIA STYLE	
30	125 / 250			50	250 x 3-DELTA		

NEMA

IEC

AMP	VOLT	POWER INLET	POWER RECEPTACLE	AMP	VOLT	POWER INLET	POWER RECEPTACLE
15/10*	125 OR 250			20/16*	125 OR 250		
AMP	VOLT	PIN & SLEEVE		AMP	VOLT	PIN & SLEEVE	
20/16*	250/230*			60/63*	250/230*		
20	250			60	250		
30/32*	250/230*			20/16*	230/400* x 3-WYE		
30	250			30/32*	230/400* x 3-WYE		

* Rating for CE products